




Dajulong No.7

复合商用卷材地板

DajuLong[®]
大巨龙弹性地板

Dajulong No.7

规格: 2.0mm × 2m × 20m



Dajulong No.7

Dimension: 2.0mm × 2m × 20m




JL07-41



JL07-42




JL07-43



JL07-44



JL07-45



JL07-46

Dajulong No.7

规格: 2.0mm × 2m × 20m



JL07-51



JL07-52



JL07-53



JL07-54



JL07-55




JL07-56

Dajulong No.7


Dimension: 2.0mm x 2m x 20m





JL07-61




JL07-62




JL07-63



JL07-71



JL07-72



JL07-73

Dajulong No.7

复合商用卷材地板



Description 规格	Standard 标准	Result 结果
Total thickness 总厚度	EN 428	2.0 mm
Wear layer thickness 耐磨层	EN 429	0.35 mm
Width 宽度	EN 426	2 m
Length of sheet 卷长	EN 426	20 m


Classification 类别

Fire rating 防火等级	GB 8624-2012	B1
Toxic testing 有害物质检测	GB 18586-2001	Good 合格
Electrical resistance 抗电阻性	EN 1081	$> 10^9-10$
Slip resistance dry 防干滑性	EN 13893	≥ 0.3
Slip resistance wet 防湿滑性	EN 51 130	R9

Performances 性能

Castor chair test 轮压测试	EN 425	No damage 合格
Colour fastness 颜色稳定性	EN ISO 105 - B02	≥ 6
Chemical products resistance 抗化学性	EN 423	Good 好
Dimensional stability 尺寸稳定性	EN 434	$\leq 0.40\%$
Curl resultant to heat 加热翘曲	EN 434	≤ 1 mm
Sound reduction 消音率	EN ISO 717/2	Approx. 4 dB
Residual indentation 残余凹陷度	EN 433	0.03 mm
Anti-bacterial and fungicidal 抗菌防霉性能		Good 好
VOC 挥发物排放量		< 10
Surface treatment 表面处理		PUR

Intertek 抗菌检测报告



FloorScore 环保检测报告



SGS 防火检测报告

